

ZESTAWIENIE STALI PROFILOWEJ

Poz.	Lp.	Przekrój	Materiał	Ilość w elem. (szt.)	Ilość elemen. (szt.)	Razem (szt.)	Długość (mm)	Masa		
								Wzrost (kg/m)	Element (kg)	Całkowita (kg)
1	L 80x80x10	S235JR/ST	1	4	4	4	11423	13,50	154,21	616,84
2	L 80x80x10	S235JR/ST	1	4	4	4	6284	13,50	84,80	339,24
3	L 90x90x10	S235JR/ST	1	4	4	4	11946	19,50	191,30	646,19
4	L 90x90x10	S235JR/ST	1	4	4	4	14284	19,50	192,83	771,84
5	L 80x80x10	S235JR/ST	1	4	4	4	10084	13,50	176,13	644,54
6	L 80x80x10	S235JR/ST	1	4	4	4	12623	13,50	170,41	681,64
7	L 70x50x7	S235JR/ST	1	4	4	4	11464	6,25	71,46	285,85
8	L 70x50x7	S235JR/ST	1	4	4	4	6104	6,25	39,40	167,80
9	L 70x50x7	S235JR/ST	1	4	4	4	11964	6,25	74,96	289,85
10	L 70x50x7	S235JR/ST	1	4	4	4	14283	6,25	89,33	367,23
11	L 70x50x7	S235JR/ST	1	4	4	4	10956	6,25	63,10	256,40
12	L 70x50x7	S235JR/ST	1	4	4	4	12653	6,25	79,96	316,83
13	L 40x40x4	S235JR/ST	1	4	4	4	290	2,42	0,70	2,81
14	L 40x40x4	S235JR/ST	1	4	4	4	398	2,42	0,92	3,28
15	L 40x40x4	S235JR/ST	1	4	4	4	390	2,42	0,94	3,18
16	L 40x40x4	S235JR/ST	1	4	4	4	446	2,42	1,08	4,82
17	L 40x40x4	S235JR/ST	1	4	4	4	502	2,42	1,21	4,88
18	L 40x40x4	S235JR/ST	1	4	4	4	598	2,42	1,36	5,40
19	L 40x40x4	S235JR/ST	1	4	4	4	614	2,42	1,48	5,94
20	L 40x40x4	S235JR/ST	1	4	4	4	670	2,42	1,62	6,49
21	L 40x40x4	S235JR/ST	1	4	4	4	726	2,42	1,76	7,02
22	L 40x40x4	S235JR/ST	2	4	8	8	780	2,42	1,89	16,10
23	L 40x40x4	S235JR/ST	1	4	4	4	681	2,42	1,65	6,89
24	L 40x40x4	S235JR/ST	1	4	4	4	562	2,42	1,41	5,69
25	L 40x40x4	S235JR/ST	1	4	4	4	482	2,42	1,17	4,67
26	L 40x40x4	S235JR/ST	1	4	4	4	382	2,42	0,92	3,70
27	L 40x40x4	S235JR/ST	1	4	4	4	286	2,42	0,69	2,76
28	L 40x40x4	S235JR/ST	1	4	4	4	288	2,42	0,68	2,74
29	L 40x40x4	S235JR/ST	1	4	4	4	346	2,42	0,63	3,04
30	L 40x40x4	S235JR/ST	1	4	4	4	406	2,42	0,99	3,89
31	L 40x40x4	S235JR/ST	1	4	4	4	470	2,42	1,14	4,59
32	L 40x40x4	S235JR/ST	1	4	4	4	536	2,42	1,34	5,36
33	L 40x40x4	S235JR/ST	1	4	4	4	606	2,42	1,44	6,16
34	L 40x40x4	S235JR/ST	1	4	4	4	696	2,42	1,59	6,97
35	L 40x40x4	S235JR/ST	1	4	4	4	770	2,42	1,74	6,97
36	L 40x40x4	S235JR/ST	2	4	8	8	782	2,42	1,89	16,14
37	L 40x40x4	S235JR/ST	1	4	4	4	731	2,42	1,77	7,08
38	L 40x40x4	S235JR/ST	1	4	4	4	690	2,42	1,65	6,88
39	L 40x40x4	S235JR/ST	1	4	4	4	628	2,42	1,52	6,09
40	L 40x40x4	S235JR/ST	1	4	4	4	578	2,42	1,40	5,69
41	L 40x40x4	S235JR/ST	1	4	4	4	527	2,42	1,28	5,10
42	L 40x40x4	S235JR/ST	1	4	4	4	478	2,42	1,16	4,83
43	L 40x40x4	S235JR/ST	1	4	4	4	428	2,42	1,04	4,16
44	L 40x40x4	S235JR/ST	1	4	4	4	380	2,42	0,92	3,68
45	L 40x40x4	S235JR/ST	1	4	4	4	331	2,42	0,80	3,20
46	L 40x40x4	S235JR/ST	1	4	4	4	283	2,42	0,69	2,74
47	L 40x40x4	S235JR/ST	1	4	4	4	234	2,42	0,69	2,75
48	L 40x40x4	S235JR/ST	1	4	4	4	186	2,42	0,66	3,44
49	L 40x40x4	S235JR/ST	1	4	4	4	138	2,42	1,03	4,12
50	L 40x40x4	S235JR/ST	1	4	4	4	89	2,42	1,21	4,82
51	L 40x40x4	S235JR/ST	1	4	4	4	40	2,42	1,38	5,82
52	L 40x40x4	S235JR/ST	1	4	4	4	642	2,42	1,95	6,91
53	L 40x40x4	S235JR/ST	1	4	4	4	714	2,42	1,73	6,21

POZ. 2.1.3. - KONSTRUKCJA POD ŚWIETLIK

Poz.	Lp.	Przekrój	Materiał	Ilość w elem. (szt.)	Ilość elemen. (szt.)	Razem (szt.)	Długość (mm)	Masa		
								Wzrost (kg/m)	Element (kg)	Całkowita (kg)
54	L 100x100x4	S235JR/ST	2	4	8	4	761	2,42	1,99	15,12
55	L 100x100x4	S235JR/ST	1	4	4	4	755	2,42	1,78	7,11
56	L 100x100x4	S235JR/ST	1	4	4	4	694	2,42	1,66	6,62
57	L 100x100x4	S235JR/ST	1	4	4	4	634	2,42	1,53	6,14
58	L 100x100x4	S235JR/ST	1	4	4	4	572	2,42	1,41	5,64
59	L 100x100x4	S235JR/ST	1	4	4	4	512	2,42	1,29	5,15
60	L 100x100x4	S235JR/ST	1	4	4	4	451	2,42	1,16	4,65
61	L 100x100x4	S235JR/ST	1	4	4	4	390	2,42	1,04	4,16
62	L 100x100x4	S235JR/ST	1	4	4	4	330	2,42	0,92	3,68
63	L 100x100x4	S235JR/ST	1	4	4	4	269	2,42	0,80	3,20
64	L 100x100x4	S235JR/ST	1	4	4	4	208	2,42	0,69	2,74
65	L 100x100x4	S235JR/ST	1	4	4	4	147	2,42	0,57	2,25
66	L 100x100x4	S235JR/ST	1	4	4	4	86	2,42	0,45	1,76
67	L 100x100x4	S235JR/ST	1	4	4	4	26	2,42	0,33	0,87
68	L 100x100x4	S235JR/ST	1	4	4	4	1170	2,42	2,65	10,28
69	L 100x100x4	S235JR/ST	1	4	4	4	1300	2,42	2,94	11,57
70	L 100x100x4	S235JR/ST	1	4	4	4	1430	2,42	3,23	12,82
71	L 100x100x4	S235JR/ST	1	4	4	4	1560	2,42	3,52	14,07
72	L 100x100x4	S235JR/ST	1	4	4	4	1690	2,42	3,82	14,89
73	L 100x100x4	S235JR/ST	1	4	4	4	1820	2,42	4,11	15,71
74	L 100x100x4	S235JR/ST	1	4	4	4	1950	2,42	4,40	16,53
75	L 100x100x4	S235JR/ST	1	4	4	4	2080	2,42	4,69	17,35
76	L 100x100x4	S235JR/ST	1	4	4	4	2210	2,42	4,98	18,17
77	L 100x100x4	S235JR/ST	1	4	4	4	2340	2,42	5,27	18,99
78	L 100x100x4	S235JR/ST	1	4	4	4	2470	2,42	5,56	19,81
79	L 100x100x4	S235JR/ST	1	4	4	4	2600	2,42	5,85	20,63
80	L 100x100x4	S235JR/ST	1	4	4	4	2730	2,42	6,14	21,45
81	L 100x100x4	S235JR/ST	1	4	4	4	2860	2,42	6,43	22,27
82	L 100x100x4	S235JR/ST	1	4	4	4	2990	2,42	6,72	23,09
83	L 100x100x4	S235JR/ST	1	4	4	4	3120	2,42	7,01	23,91
84	L 100x100x4	S235JR/ST	1	4	4	4	3250	2,42	7,30	24,73
85	L 100x100x4	S235JR/ST	1	4	4	4	3380	2,42	7,59	25,55
86	L 100x100x4	S235JR/ST	1	4	4	4	3510	2,42	7,88	26,37
87	L 100x100x4	S235JR/ST	1	4	4	4	3640	2,42	8,17	27,19
88	L 100x100x4	S235JR/ST	1	4	4	4	3770	2,42	8,46	28,01
89	L 100x100x4	S235JR/ST	1	4	4	4	3900	2,42	8,75	28,83
90	L 100x100x4	S235JR/ST	1	4	4	4	4030	2,42	9,04	29,65
91	L 100x100x4	S235JR/ST	1	4	4	4	4160	2,42	9,33	30,47
92	L 100x100x4	S235JR/ST	1	4	4	4	4290	2,42	9,62	31,29
93	L 100x100x4	S235JR/ST	1	4	4	4	4420	2,42	9,91	32,11
94	L 100x100x4	S235JR/ST	1	4	4	4	4550	2,42	10,20	32,93
95	L 100x100x4	S235JR/ST	1	4	4	4	4680	2,42	10,49	33,75
96	L 100x100x4	S235JR/ST	1	4	4	4	4810	2,42	10,78	34,57
97	L 100x100x4	S235JR/ST	1	4	4	4	4940	2,42	11,07	35,39
98	L 100x100x4	S235JR/ST	1	4	4	4	5070	2,42	11,36	36,21
99	L 100x100x4	S235JR/ST	1	4	4	4	5200	2,42	11,65	37,03
100	L 100x100x4	S235JR/ST	1	4	4	4	5330	2,42	11,94	37,85
101	L 100x100x4	S235JR/ST	1	4	4	4	5460	2,42	12,23	38,67
102	L 100x100x4	S235JR/ST	1	4	4	4	5590	2,42	12,52	39,49
103	L 100x100x4	S235JR/ST	1	4	4	4	5720	2,42	12,81	40,31
104	L 100x100x4	S235JR/ST	1	4	4	4	5850	2,42	13,10	41,13
105	L 100x100x4	S235JR/ST	1	4	4	4	5980	2,42	13,39	41,95
106	L 100x100x4	S235JR/ST	1	4	4	4	6110	2,42	13,68	42,77
107	L 100x100x4	S235JR/ST	1	4	4	4	6240	2,42	13,97	43,59